



solaire
A Lagnuvo Initiative

X3-AELIO-HV

49.9kW/50kW/60kW/61kW
38.4kWh-215kWh

Solaire Split C&I Energy Storage Solution

Global: +254 716 506554 / +254 738 926668

 www.solairerafrica.com

 info@solairerafrica.com

X3-AELIO



Flexible Configuration

Customizable battery setup: batteries can be flexibly configured according to customer site requirements, supporting indoor and rack-mounted installations.

Parallel operation: supports up to 10 parallel systems, meeting power requirements from 49.9 kW to 600 kW on grid.

Battery options: two-way battery connector, catering to single system capacities ranging from 38.4 kWh to 215 kWh.

PV oversizing: supports up to 200% PV oversizing.

Safe and Reliable

Three-phase unbalance: inverter supports 100% three-phase unbalance.

Long-term overload: inverter supports 110% long-term overload.

Seamless switching: inverter supports 10ms on-grid/off-grid switching, ensuring uninterrupted power supply for onsite loads.

Intelligent and Convenient

Remote monitoring: supports web/app remote data viewing and remote OTA updates.

Versatile operating modes: supports various operating modes to meet different application scenarios such as self-consumption, peak shaving, and demand management.

VPP integration: supports VPP through IEEE 2030.5, OpenADR*.

Generator control: work seamlessly with generator to save fuel and back up

* Feature to be upgraded in the future

	X3-AELIO-49.9K	X3-AELIO-49.9K-P	X3-AELIO-50K	X3-AELIO-60K	X3-AELIO-61K
PV INPUT					
Max. recommended PV array power	100 kWp	120 kWp	100 kWp	120 kWp	
Max. PV input voltage ^①	1000 V				
Rated PV input voltage	650 V				
MPPT voltage range ^②	160 ~ 950 V				
Start-up voltage	180 V				
No. of MPP trackers / strings per MPP tracker	5 / 2	6 / 2	5 / 2	6 / 2	
Max. input current per MPPT	40 A				
Max. input short circuit current per MPPT	50 A				
AC INPUT & OUTPUT (ON-GRID)					
Rated output power	49.9 kW	49.9 kW	50 kW	60 kW	61 kW
Rated output current	75.7 A @ 220 V 72.4 A @ 230 V	75.7 A @ 220 V 72.4 A @ 230 V	75.8 A @ 220 V 72.5 A @ 230 V	91.0 A @ 220 V 87.0 A @ 230 V	92.5 A @ 220 V 88.5 A @ 230 V
Max. output apparent power	49.9 kVA	49.9 kVA	55.0 kVA	66.0 kVA	66.0 kVA
Max. output continuous current	75.7 A @ 220 V 72.4 A @ 230 V	75.7 A @ 220 V 72.4 A @ 230 V	83.4 A @ 220 V 79.8 A @ 230 V	100.0 A @ 220 V 95.7 A @ 230 V	100.0 A @ 220 V 95.7 A @ 230 V
Rated AC voltage	3 / N / PE, 220 / 380 V 3 / N / PE, 230 / 400 V				
Rated AC frequency	50 Hz / 60 Hz				
AC frequency range ^③	50 ± 5 Hz / 60 ± 5 Hz				
Adjustable power factor range	~1 (0.8 leading to 0.8 lagging)				
THDi (rated power)	< 3%				

X3-AELIO-49.9K

X3-AELIO-49.9K-P

X3-AELIO-50K

X3-AELIO-60K

X3-AELIO-61K

BATTERY					
Battery type	LFP				
Battery voltage range	180 ~ 820 V				
Max. charge / discharge current	160 A (80 A × 2)				
	EPS (OFF-GRID) OUTPUT				
Rated EPS output voltage, frequency	3 / N / PE, 220 / 380 V, 50 Hz / 60 Hz 3 / N / PE, 230 / 400 V, 50 Hz / 60 Hz				
Rated EPS output power	49.9 kVA	49.9 kVA	50.0 kVA	60.0 kVA	61.0 kVA
Max. EPS output power	75 kVA, 10s	75 kVA, 10s	75 kVA, 10s	90 kVA, 10s	90 kVA, 10s
Switchover time	< 10 ms				
	EFFICIENCY				
Max. efficiency	98.0%				
European efficiency	97.2%				
	GENERAL				
Ingress protection	IP66				
Operation temperature range	-35 ~ 60°C (derating +45°C)				
Max. operating altitude	3000 m				
Relative humidity	0 ~ 100% RH (condensing)				
Overvoltage category	Mains: III, Battery: II, PV: II				
Dimensions (W × H × D)	670 × 820 × 257 mm				
Net weight	< 100 kg	< 105 kg	< 100 kg	< 105 kg	
Cooling concept	Smart air cooling				
Communication interfaces	RS485-Meter, RS485-Monitor, RS485-Parallel (daisy-chain), CAN-BMS, CAN-Parallel (daisy-chain), USB, DI×2, DO×1, RCR (DI×4), DRM				
Topology	Non-isolated				
Certifications	CE, VDE4105, G99, AS4777, EN50549, CEI 0-21, IEC61727, PEA/MEA, NRS-097-2-1, RD1699, TOR				
PROTECTION					
Over / under voltage protection	Yes				
DC isolation protection	Yes				
DC reverse-polarity protection	Yes				
Grid monitoring	Yes				
DC injection monitoring	Yes				
Back feed current monitoring	Yes				
Residual current detection	Yes				
Over temperature protection	Yes				
Active anti-islanding method	Frequency shift				
Surge protection (DC / AC)	DC: Type II, AC: Type II				
Arc-fault circuit interrupter (AFCI)	Optional				
AC auxiliary power supply (APS)	Built-in				

① The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage inverter

② Input voltage exceeding the MPPT voltage range may triggers inverter protection

③ The AC frequency range may vary from different country codes